



- STANDARD SWITCH FEATURES:
- 3 POLE KNIFE TYPE - NON FUSIBLE
 - 1000 VOLT INSULATION CLASS
 - NON FUSIBLE
 - NON LOAD-BREAK
 - NEMA 12 ENCLOSURE
 - EXTERNAL PADLOCKABLE HANDLE OPERATOR
 - TOP ENTRY, BOTTOM EXIT
 - ANSI 61 GRAY FINISH

AVAILABLE OPTIONS:

DESCRIPTION OF OPTIONS	SUFFIX
AUXILIARY SWITCHES QTY 2; TWO AUXILIARY SWITCHES FORM 'C', (C) CLOSED AND (O) OPEN (NOT WIRED)	1X
AUXILIARY SWITCHES QTY 4; FOUR AUXILIARY SWITCHES FORM 'C', (C) CLOSED AND (O) OPEN (NOT WIRED)	2X
TERMINAL BOARD	TB
AUXILIARY SWITCHES WIRED TO A TERMINAL BOARD	
KEY INTERLOCK PROVISION IN THE OPEN POSITION	K1
KEY INTERLOCK PROVISION IN THE CLOSED POSITION	K2
KEY INTERLOCK PROVIDED IN THE OPEN AND CLOSED POSITION	K3
KEY INTERLOCK PROVIDED BY FILNOR - SINGLE KEY	DRIVER BY DESCRIPTION
POLYCARBONATE WINDOW IN DOOR	V
NEMA 3R ENCLOSURE	3R
NEMA 4 ENCLOSURE	4
NEMA 4X ENCLOSURE	4X

TERMINAL DIMENSIONS		
AMP	A	B
200	5.69	4.09
400	5.81	4.94
600	6.06	5.53

Filnor Inc.
 P.O. BOX 5200
 ALLIANCE, MO 64801

UNLESS OTHERWISE SPECIFIED, THE FOLLOWING DISCONNECT SWITCH LAYOUT IS FOR 200 THRU 600 AMP

REV	DATE	BY	REASON
1			
2			
3			
4			
5			
6			
7			

DESIGNED BY: J.S. DATE: 10/22/07
 CHECKED BY: J.R.H. DATE: 10/22/07
 APPROVED BY: [Signature] DATE: 10/22/07

QUANTITY: 2000 PERS
 DRAWING NO: GMZ27345